

Europäisches Patentamt
European Patent Office
Office européen des brevets



(11) EP 0 961 386 A1

(12) EUROPEAN PATENT APPLICATION

(43) Date of publication:
01.12.1999 Bulletin 1999/48

(51) Int. Cl.⁶: H02K 3/34, H02K 15/02

(21) Application number: 99109772.6

(22) Date of filing: 18.05.1999

(84) Designated Contracting States:
AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU
MC NL PT SE
Designated Extension States:
AL LT LV MK RO SI

(30) Priority: 25.05.1998 JP 14300898
26.06.1998 JP 18075598

(71) Applicant: Denso Corporation
Kariya-city, Aichi-pref., 448-8661 (JP)

(72) Inventors:
• Kusase, Shin,
c/o Denso Corporation
Kariya-city, Aichi-pref. 448-8661 (JP)
• Umeda, Atsushi,
c/o Denso Corporation
Kariya-city, Aichi-pref. 448-8661 (JP)


• Naka, Yoshio,
c/o Denso Corporation
Kariya-city, Aichi-pref. 448-8661 (JP)
• Matsubara, Shinichi,
c/o Denso Corporation
Kariya-city, Aichi-pref. 448-8661 (JP)
• Shiga, Tsutomu,
c/o Denso Corporation
Kariya-city, Aichi-pref. 448-8661 (JP)
• Ishida, Hiroshi,
c/o Denso Corporation
Kariya-city, Aichi-pref. 448-8661 (JP)

(74) Representative:
R.A. KUHNEN & P.A. WACKER
Patentanwalts-gesellschaft mbH
Alois-Steinecker-Strasse 22
85354 Freising (DE)

(54) Stator of ac generator for vehicle

(57) In a stator of an ac generator for vehicle, a plurality of insulators (34) are disposed in the slots (35) of the stator to insulate the stator winding from the stator core (32). Each of the insulators (34) has a smooth edge at one end and a stopper portion (36) at the other end. The stopper portion (36)s project from an axial end of the stator core (32) from which conductor segments (33, 233) of the stator winding are inserted. The conductor segments (33, 233) can be inserted into the slots (35) with the smooth edges being at the head and can be easily positioned in the slots (35) by the stopper.

FIG.12



EP 0 961 386 A1

Description

[0001] The present invention relates to a stator of an ac generator for a passenger car, a truck, or other vehicles that is driven by an internal combustion engine.

[0002] It is known that a stator winding of an ac generator for a vehicle is formed of a plurality of conductor segments which are welded together. WO92/06527 discloses an example of such a stator winding, in which each of the conductor segments is inserted from one end of the stator core, the ends of conductor segments are welded to one another at the other end of the stator core. Usually, insulators are inserted into slots of the stator core. JP-A-4-17539 discloses insulators, each of which has a U-shape cross section and folded lips formed at opposite ends thereof. The folded lips position the insulator in the slot easily.

[0003] However, it is difficult to insert the insulators into the slot because the insulator disclosed in JP-A-4-17539 has folded lips at opposite ends thereof. While it is easy to insert an insulator having no such folded lips into the slot, it is difficult to position such an insulator in the axial direction. If an attempt is made to fold an end of the insulators after the conductor segments are inserted into the slots, the folded portion may be damaged due to folding pressure. Thus, the conductor segments can not be insulated from the stator core very well by a single sheet of insulator film.

[0004] Therefore, an object of the invention is to provide an improved stator of an ac generator for a vehicle in which insulators can be installed and positioned easily without damage.

[0005] According to a main feature of the invention, each of a plurality of insulators disposed in slots has a smooth end portion extending from one axial end of the stator core and a stopper engaging the other axial end of the stator core.

[0006] In the ac generator, stator winding may be composed of a plurality of conductor segments having a U-turn portion disposed at one end of the stator core, and the stopper portion is disposed at the same end as the U-turn portion.

[0007] Other objects, features and characteristics of the present invention as well as the functions of related parts of the present invention will become clear from a study of the following detailed description, the appended claims and the drawings. In the drawings:

Fig. 1 is a cross-sectional view illustrating an ac generator for a vehicle according to a first embodiment of the invention;

Fig. 2 is a perspective view of a U-shaped conductor segment forming a part of a stator winding of the stator according to the first embodiment;

Fig. 3 is a fragmentary cross-sectional view of the stator according to the first embodiment;

Fig. 4 is a perspective view illustrating an insulator to be inserted into one of slots of a stator core of the

stator according to the first embodiment;

Fig. 5A is a fragmentary side view of a portion of the stator core and an insulator, Fig. 5B is a fragmentary side view of a portion of the stator with conductor segments disposed in one of the slots;

Fig. 6 is a fragmentary side view of a portion of the stator according to the first embodiment of the invention;

Fig. 7 is a perspective view illustrating coil ends disposed at opposite ends of the stator according to the first embodiment;

Fig. 8 is a fragmentary cross-sectional view of a portion of the stator according to a second embodiment of the invention;

Fig. 9 is a fragmentary perspective view of the stator according to the second embodiment;

Fig. 10 is a perspective view illustrating a modified conductor segment;

Fig. 11 is a fragmentary view of the stator having a plurality of the modified conductor segments shown in Fig. 10;

Fig. 12 is a perspective view illustrating a variation of the insulator to be inserted into one of slots of a stator core of the stator according to the first embodiment; and

Fig. 13 is a perspective view illustrating a variation of an insulator to be inserted into one of slots of a stator core of the stator according to the first embodiment.

[0008] An embodiment of the present invention is described with reference to the appended drawings.

[0009] As shown in Fig. 1, ac generator 1 according to a first embodiment of the invention includes stator 2, rotor 3, frame 4, rectifier 5 and so on.

[0010] Stator 2 is composed of stator core 32, a plurality of conductor segments 33 and a plurality of insulators 34. Stator core 32 is a lamination of steel plates having a number of slots formed inside thereof. The portion of conductor segments projecting from stator core 32 form coil ends 31.

[0011] Rotor 3 has field coil 8, a pair of pole cores 7, and shaft 6. Each of the pair of pole cores 7 has six claw pole pieces extending axially to enclose field coil 8. Field coil 8 is composed of a cylindrically-wound insulation-coated copper wire. Axial flow type cooling fan 11 is welded to the front side pole core 7 to supply cooling air from the front side thereof in both the radial and axial directions. Centrifugal cooling fan 12 is welded to the rear side pole core 7 to supply cooling air from the rear side thereof radially outward.

[0012] Frame 4 accommodates stator 2 and rotor 3 and supports rotor 3 to rotate with shaft 6. Stator 2 is fixed to frame 4 around the pair of pole cores 7 at a certain gap therefrom. Frame 4 has air discharge vents 42 at portions opposite coil ends 31 of stator 2 and air intake vents 41 at the axial ends thereof.

[0013] AC generator 1 described above is rotated in a

certain direction by an engine (not shown) via a belt and a pulley 20. When field coil 8 is energized by an outside power source, pole cores 7 is excited so that the stator winding provides a three-phase ac voltage. Accordingly, rectifier 5 provides a certain amount of dc current at the output terminals.

[0014] As illustrated in Fig. 2, conductor segments 33 is a U-shaped member made of copper bar or plate. Conductor segment 33 has inner conductor portion 33a, outer conductor portion 33b and U-turn portion 33c. Each of inner conductor portion 33a and outer conductor portion 33b has straight inner portion disposed in slot 35 and outer portion disposed outside slot 35.

[0015] A pair of conductor segments 33 is disposed in each one of slots 35 and connected to one another in a well known manner to form the stator winding. As illustrated in Fig. 3, inner and outer conductor portions 33a, 33b of conductor segment 33 has rectangular cross-section. The circumferential sides of conductor segment 33 are longer than its radial sides. Conductor segments 33 are coated with insulation film to insulate one segment from another. Insulators 34 insulate conductor segments 33 from the stator core 32.

[0016] Column-shaped insulator 34 is made of a resinous sheet, which is rolled to fit the slot as shown in Fig. 4. Insulator 34 has a smooth edge at one end and outwardly folded lip 36 at the other end thereof. Insulator 34 is inserted into slot 35 in the axial direction with the smooth edge being at the head. Folded lip 36 functions as a stopper or positioner of insulator 34. Insulator 34 is inserted into slot 35 until folded lip 36 engages an end of stator core 32 so that both ends of insulator 34 can project from stator core 32 as shown in Fig. 5A. Subsequently, conductor segments 33 are inserted therein as shown in Fig. 5B and welded to form stator winding. Accordingly, conductor segments 33 are insulated from edge portions of stator core 32 by the projected portions of insulator 34. Here, folded lip 36 of insulator 34 is disposed at the side of stator core 32 where U-turn portion 33c is located. In other words, conductor segments 33 are inserted in the same direction as insulators 34 are inserted.

[0017] As illustrated in Fig. 6, U-turn portions 33c are disposed at one axial end of stator core 32 and opposite ends 33d are disposed at the other end thereof. Each of conductor segments 33 has slant portion 33e forming coil end 31 at one end of stator core 2. Slant portions 33e of conductor segments 33 disposed in the outer layers extend in the same direction, while slant portions 33e disposed in the inner layers extend in the different direction. Ends 33d of conductor segments 33 are welded by ultrasonic wave welder or arc welder, or are soldered or mechanically connected.

[0018] As shown in Fig. 4, one of insulators 34 is inserted to each of slots 35. Conductor segments 33 are made of copper plates, each of which is bent by a press machine to form a U-shape. A number of U-shaped conductor segments 33 are lined up so that U-turn portions

33c can be disposed at the same end of stator core 32. Conductor segments 33 are press-fitted into respective slots 35 so that outer and inner conductor portions 33b, 33a can fit the parallel walls of slot 35 via insulators 34 on the opposite surfaces thereof. As shown in Fig. 3, outer conductor portions 33b are inserted into the inner side of slots 35 that are insulated by insulators 34, and inner conductor portions 33a are inserted into the outer side of slots 35. Thereafter, two end portions 33d are bent in the opposite directions respectively to connect to end portions 33d of other conductor segments 33 in different layers.

[0019] Because insulator 34 has folded lip 36 at one end thereof and the other smooth end, insulator 34 can be inserted into the slot very easily. Moreover, assembling tools can be arranged in the axial direction if insulators 34 are inserted in the same axial direction as conductor segments 33 are inserted.

[0020] Thus, folded lips 36 engage the end of stator core 32 when conductor segments 33 are fully inserted into slots 35 to position insulators 34 correctly.

[0021] Folded lips 36 can be located opposite the U-turn portion or the end from which conductor segments 33 are inserted. Folded lips 36 protect insulators 34 from pressure applied when end portions 33d are bent.

[0022] The number of conductor segments in each of the slots can be increased. A stator according to a second embodiment of the invention has four conductor segments 133 each of the slots as shown in Fig. 8. Four conductor segments 133 are lined up in the radial direction in each of slots 135 and connected in the manner illustrated in Fig. 9. Each of four conductor segments 133 extends from one of slots 135 in the alternately opposite direction. Conductor segments 133 on this side of Fig. 9 extend clockwise and those on the opposite side extend counterclockwise. End portion 133d of one conductor segment 133 is connected to end portion 133d of another conductor segment 133 spaced apart at a certain pitch. One of conductor segments 133 in the innermost layer is connected to another in the second inner layer, and one of conductor segments 133 in the third layer is connected to another in the outermost layer. Fig. 9 illustrates a portion of stator opposite the end from where conductor segments are inserted and folded lips 136 of insulators 134.

[0023] U-shaped conductor segment 33 can be substituted by a pair of turn-less conductor segments, which is welded after being assembled. Fig. 10 is a perspective view which illustrates I-shaped or J-shaped conductor segment 233. Conductor segment 233 has straight inside portion 233h and outside portions 233i extending outward from opposite ends of inside portion 233h. One of outside portions 233i is bent from the dotted state. End portion 233d of one conductor segment 233 is connected to end portion 233d of another conductor segment 233 disposed in another slot to form a stator winding. Conductor segments 233 are simple in shape and easy to manufacture. Because each of con-

ductor segments 233 corresponds to one of insulators 34, it is easy to insert insulators 34 and conductor segments 233 into slots 35.

[0024] Insulator 34 described above can be substituted by open insulator 341 having flared lip 361 shown in Fig. 12 or by closed insulator 342 having flared lip 362 shown in Fig. 13. Flared lips 361, 362 can be formed after the insulators are inserted into slots 35 easily without interference with each other. Each of flared lips 361 and 362 functions as a stopper to prevent the insulator from being dragged into slot 35 when conductor segment 33 is fully inserted into slot 35.

[0025] As shown in Fig. 13, overlapping portion 342a of closed insulator 342 is disposed remote from the opening of slot 35. This structure is effective to shut out water.

[0026] In the foregoing description of the present invention, the invention has been disclosed with reference to specific embodiments thereof. It will, however, be evident that various modifications and changes may be made to the specific embodiments of the present invention without departing from the broader spirit and scope of the invention as set forth in the appended claims. Accordingly, the description of the present invention in this document is to be regarded in an illustrative, rather than restrictive, sense.

Claims

1. A stator of an ac generator for vehicle comprising
 - a stator core (32) having a plurality of slots (35),
 - a stator winding disposed in said slots (35), and
 - a plurality of column-shaped insulators (34) disposed in said plurality of slots (35) to insulate said stator winding from said stator core (32), wherein
 - each of said plurality of insulators (34) has an outer periphery fitted to one of said plurality of slots (35), a smooth edge extending from one end of said stator core (32) and a stopper portion (36) engaging the other end of said stator core (32).
2. The ac generator as claimed in claim 1, wherein
 - said stator winding comprises a plurality of conductor segments (33, 233) each of which has a U-turn portion (33c) disposed at one end of said stator core (32).
3. The ac generator as claimed in claim 2, wherein
 - each of said plurality of conductor segments (33, 233) has approximately the same cross-sectional shape as said plurality of slots (35).
4. The ac generator as claimed in claim 1, wherein
 - said stopper portion (36) is disposed at the same end of said stator core (32) as said U-turn portion (33c).
5. The ac generator as claimed in claim 1, wherein
 - said stopper portion (36) comprises a folded lip (36) of an end portion of said insulator (34).

FIG. 1




FIG. 2




FIG. 3




FIG. 6




FIG. 4




FIG. 5A




FIG. 5B




FIG. 7




FIG. 8




FIG. 9




FIG. 10




FIG. 11




FIG. 12





FIG. 13





European Patent
Office

EUROPEAN SEARCH REPORT

Application Number
EP 99 10 9772

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int.Cl.6)
X	PATENT ABSTRACTS OF JAPAN vol. 008, no. 256 (E-280), 22 November 1984 (1984-11-22) & JP 59 129548 A (NIPPON DENSO KK), 25 July 1984 (1984-07-25) * abstract *	1-3	H02K3/34 H02K15/02
X	PATENT ABSTRACTS OF JAPAN vol. 008, no. 243 (E-277), 8 November 1984 (1984-11-08) & JP 59 122330 A (HITACHI SEISAKUSHO KK), 14 July 1984 (1984-07-14) * abstract *	1, 5	
X	PATENT ABSTRACTS OF JAPAN vol. 007, no. 280 (E-216), 14 December 1983 (1983-12-14) & JP 58 157349 A (TOKYO SHIBAURA DENKI KK), 19 September 1983 (1983-09-19) * abstract *	1	
X	PATENT ABSTRACTS OF JAPAN vol. 010, no. 233 (E-427), 13 August 1986 (1986-08-13) & JP 61 066553 A (MITSUBISHI ELECTRIC CORP), 5 April 1986 (1986-04-05) * abstract *	1, 5	TECHNICAL FIELDS SEARCHED (Int.Cl.6) H02K
X	US 3 745 394 A (MASON L) 10 July 1973 (1973-07-10) * figure 3 *	1, 5	
X	EP 0 006 514 A (RAPIDSYN CO) 9 January 1980 (1980-01-09) Abstract * figure 7 *	1	
-/--			
The present search report has been drawn up for all claims			
Place of search THE HAGUE		Date of completion of the search 31 August 1999	Examiner Zoukas, E
CATEGORY OF CITED DOCUMENTS X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons & : member of the same patent family, corresponding document			

EPO FORM 1503/03 B2 (P4C01)



European Patent
Office

EUROPEAN SEARCH REPORT

Application Number
EP 99 10 9772

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int.Cl.6)
A	WO 92 06527 A (BOSCH GMBH ROBERT) 16 April 1992 (1992-04-16) Abstract * figure 3 *	2	
A	FR 1 091 544 A (SOCIÉTÉ DE PARIS & DU RHÔNE) 13 April 1955 (1955-04-13) * figures 1-4 *	2,3	
			TECHNICAL FIELDS SEARCHED (Int.Cl.6)
The present search report has been drawn up for all claims			
Place of search THE HAGUE		Date of completion of the search 31 August 1999	Examiner Zoukas, E
CATEGORY OF CITED DOCUMENTS X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons & : member of the same patent family, corresponding document			

EPO FORM 1503 03 92 (P4C01)

**ANNEX TO THE EUROPEAN SEARCH REPORT
ON EUROPEAN PATENT APPLICATION NO.**

EP 99 10 9772

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report. The members are as contained in the European Patent Office EDP file on
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

31-08-1999

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
JP 59129548 A	25-07-1984	NONE	
JP 59122330 A	14-07-1984	NONE	
JP 58157349 A	19-09-1983	NONE	
JP 61066553 A	05-04-1986	NONE	
US 3745394 A	10-07-1973	DE 1763668 A FR 1574500 A GB 1194085 A JP 54007921 B US 3514836 A US 3634932 A	18-11-1971 11-07-1969 10-06-1970 11-04-1979 02-06-1970 18-01-1972
EP 0006514 A	09-01-1980	US 4217690 A JP 55005096 A	19-08-1980 14-01-1980
WD 9206527 A	16-04-1992	DE 4031276 A DE 9017835 U	09-04-1992 12-03-1992
FR 1091544 A		NONE	

EPO FORM P0459

For more details about this annex : see Official Journal of the European Patent Office, No. 12/82